

Products Support Divisions Where to Buy About Parker

Home Products Fuel and Gas Hose - Master LPG Hose - SS25UL

LPG Hose - SS25UL



Parker's SS25UL hose is for low pressure LPG service up to 350psi. It meets UL Standard 21 certification and provides an oil and LPG resistant synthetic fiber cover. Approved operating temperature range of -40°F to + 250°F. Sizes -4 through -12.

Choose attributes to view part number:

Reset Attributes

Where to Buy

Email Product Bookmark Print Page

Contact Us

HOSE PRODUCTS DIV

30240 LAKELAND BLVD WICKLIFFE OH UNITED STATES 44092

Ph:4409435700

Fax:4409433129

Email

Print Tech Specifications	
Performance Characteristics	
Media	Liquefied petroleum gas
Maximum Working Pressure (psi)	350
Hose I.D. Maximum (inch)	5/8
Maximum Working Pressure (MPa)	2,4
Minimum Bend Radius (inch)	Meets SAE requirements
Minimum Bend Radius (mm)	Meets SAE requirements
Material - Hose Inner Tube	Synthetic rubber
Material - Hose reinforcement	One fiber and one steel braid
Material - Cover	Fiber braid
Meets Industry Standards	AGA-AS / NZS 1869D / UL STANDARD 21
Compatible Fittings	20,22 or 26 series

About Parker Contact Parker Careers Working With Parker Investors News ParkerStore™ Brands

© Parker Hannifin Corp 2013 Site Map Safety Privacy Policies Terms & Conditions

ENGINEERING YOUR SUCCESS.

1 of 1 5/12/13 9:57 AM